ROTAIR®




MDVN 37 P


PORTABLE COMPRESSOR

SUPER SILENT | POWERFUL & COMPACT



WEIGHT (with brakes)	660 Kg	1455 lbs
WEIGHT (without brakes)	650 Kg	1433 lbs





- Design with modern, slender and aggressive line
- Electro-galvanized bodywork and chassis with advanced painting procedure to grant an excellent preservation through time
- Compact dimensions for easy handling and optimum dimensions / delivered power ratio
- Light weight
- Filters “spin-on” type for quick maintenance
- Full accessibility for easy and rapid maintenance and service

OPTIONS AND ACCESSORIES:

Drawbar with or without brakes, caravan-type ball connection - Skid version
Clog indicator for engine air filter - Fuel indicator
Sandblasting kit (cooler for compressed air cooling and dew separator)
Line oiler for pneumatic tools - Warming for compressed air
Exclusive ROTAIR “FUEL SAVING SYSTEM” (saving up to 20% of fuel)

ISO 9001
BUREAU VERITAS Certification
Company certified ISO 9001:2008

CE

A NEW WORKING CONCEPT!

MDVN 37 P TECHNICAL DATA



- Exclusive pneumatic control system, developed by ROTAIR, to adjust automatically engine revs, depending on the air to be delivered. This system is highly reliable and ensures fuel consumption saving
- Start/stop "INTELLIGENT SYSTEM", exclusive from ROTAIR, to prevent the risk of incorrect procedures during specific functioning
- Air/oil separator filter, highly oversized, can guarantee an excellent air/oil separation
- The air and oil filters of the compressor and the air and oil filters of the engine are independent
- Single stage oversized air filter for compressor part, to guarantee good filtering of the air intake by airend. As option, Two-stage air filter
- Two-stage air filter for engine part
- Combined radiator allowing both compressor oil cooling and engine liquid cooling

THE RESPECT OF ORDINARY MAINTENANCE INTERVALS AND THE USE OF GENUINE SPARE PARTS ENSURE CONSTANT AND OPTIMAL PERFORMANCES AND A RELIABLE DURABILITY THROUGH TIME.

COMPRESSOR

Operating pressure	7 bar 102 psi	10 bar 145 psi	12 bar 174 psi
Free air delivery	3600 lt/min 127 cfm	2900 lt/min 102 cfm	2250 lt/min 79 cfm
Possibility to have also other operating pressures up to 14/15 bar and Dual Pressure			
Minimum working pressure	5 bar – 73 psi		
Drive system engine-airend	Direct Drive		
Compressor cooling system	Air/Oil		
Oil cooling capacity	7 lt		
Air outlet temperature	40°C – 105°F + Ambient temperature		
Outlet valves	2 x 3/4"		
Noise level EECno 2000/14	< 96 LWA		
Battery capacity	12Vcc- 400A-70Ah (EN)		
Fuel tank capacity	40 lt		
Consumes	4,90 lt/ hour (8,20 working hours)		

DIESEL ENGINE

Engine make	PERKINS
Engine type	403D-15
Engine system	4 stokes - Inline - Indirect Injection
Displacement	1496 cc
N. cylinders	3
Aspiration	Natural
Max engine power@3000 RPM	25,0 kW – 34,0 HP
Max engine speed	3000 RPM
Min engine speed	1900 RPM
Cooling system	Water
Cooling system capacity	5 lt
Lubrication system	Oil
Lubrication system capacity	5 lt

ENVIRONMENTAL CONDITIONS	(Standard version*)
Max ambient temperature	50°C – 122°F
Max altitude	1800 mt a.s.l.
Min working temperature	-10°C – 14°F

** For versions with different operating pressures or for requests of machines to be used under particular ambient temperature conditions, data have to be previously asked to our technical dept.*

** All images and pictures are indicative. Data can be changed without prior notice.*

A NEW WORKING CONCEPT!

PORTABLE COMPRESSOR
SUPER SILENT
POWERFUL & COMPACT

ROTAIR®
TECHNOLOGY AND ENGINEERING SOLUTIONS
Via Bernezzo, 67 - 12023 Caraglio (Cn) ITALY
Tel: +39 0171.619676 / Fax: +39 0171.619677
www.rotairspa.com • info@rotairspa.com